VP730

17" THINEDGE™ LCD MONITOR
WITH ULTRA-FAST 8MS CLEARMOTIV™ VIDEO RESPONSE

The focus of attention.

The VP730 provides great viewing for graphics professionals, corporate executives or power gamers – and thanks to its THINEDGE ULTRA-SLIM BEZEL DESIGN, requires only the minimum of desktop real estate. It is suitable for multiple-display configurations, and delivers strikingly clear, digital high-definition images for powerful multi-tasking and mixed-media data analysis. ClearMotiv™ 8ms broadcast-quality video response and wide XtremeView™ viewing angles together with the option to adjust the HEIGHT, PIVOT, TILT AND SWIVEL settings make it an ergonomic masterpiece.
In addition, generous connectivity possibilities are assured with multiple digital/analogue inputs.

FEATURES NOT SEEN BEFORE ON A 17" DISPLAY

- **ThinEdge ultra-slim 16mm bezel**
  Maximise display productivity with ThinEdge design that enhances the visual experience with clean, minimalist borders around the active image area.
- **Ideal for multiple-monitor setups**
  Display continuous images in multiple-panel setups. ThinEdge minimises bezel gaps between panels.
- **Pivot, height and wall-mount configurations**
  VESA® wall-mount interface (100mm) and detachable base for ergonomic flexibility with pivot, height, tilt and swivel adjustments.
- ***OPTI**SYNC* **multiple analogue/digital inputs**
  Includes one DVI-D and two analogue inputs for wide compatibility with and optimisation of a variety of video sources.
- **Integrated power supply with hard power switch**
- **TCO'03 and ENERGY qualified**
- **PerfectSuite™**
  Control software[2] featuring colour calibration, asset management and theft deterrence.
- **1280 x 1024 native resolution**
- **High contrast and brightness**
  500:1 contrast ratio (typ.) and 300cd/m² brightness (typ.)
- **ClearMotiv™ technology**
- **XtremeView™ performance**
- **sRGB compliant**
- **Kensington security slot**

MORE THAN 2000 AWARDS
ViewSonic
Products, Programs, and Services

ViewSonic®
the choice of professionals

ViewSonic
the choice of professionals

VP730

VIEWSONIC® 17" THINEDGE™ LCD MONITOR

LCD PANEL	Type	17" TN colour TFT active matrix SXGA LCD
	Display Area	338mm (horizontal) x 270mm (vertical), 43.2cm diagonal
	Pixel Pitch	0.264mm
	Optimum Resolution	1280 x 1024
	Bandwidth	135MHz
	Contrast Ratio	500:1 (typ.)
	Viewing Angle	140° horizontal, 130° vertical (at 10:1) 160° horizontal, 160° vertical (at 5:1)
	Response Time	8ms (typ.)
	Colour Support	16.7M (8bit)
	Brightness	300cd/m^2 (typ.)
	Panel Surface	Anti-glare
VIDEO INPUT	Analogue	RGB analogue (0.7/1.0 Vp-p , 75 ohms)
	Digital	DVI-D (TMDS, 100 ohms)
	Frequency	F_h: 24-82kHz, f_v: 50-85Hz
	Synchronisation	H/V separated (TTL), composite, sync on green
COMPATIBILITY	PC	Compatible from VGA up to 1280 x 1024 non-interlaced (max. 75Hz)
	Mac®[1]	Power Mac™ up to 1280 x 1024 (max. 75Hz)
CONNECTOR	Analogue	2 x 15-pin mini D-sub (detachable cable)
	Digital	Digital DVI-D (detachable cable)
	Power	3-pin plug (CEE22)
POWER	Voltage	AC 100–240V, 50–60Hz (Auto-Switch), internal power supply
	Consumption	35 watt (max.), ≤ 1 watt in suspend mode
ERGONOMICS	Tilt	Down 5°, up 20°
	Swivel	270° (135° left/right)
	Pivot	0°~90°
	Height Adjustment	0~135mm
CONTROLS	Basic	Soft power, menu [1] , down, up, select [2], main power
	OSD	Auto image adjust, contrast, brightness, input select (D-sub 1, D-sub 2, DVI), colour adjust (sRGB, 9300K, 7500K, 6500K, 5400K, 5000K, user RGB), information (resolution, H/V frequency, pixel clock, model number, serial number), manual image adjust (H/V position, H size, fine tune, sharpness), setup menu (language, resolution notice, OSD position, OSD timeout, OSD background, OSD pivot), auto white balance, OSD/power lock, memory recall
OPERATING-CONDITIONS	Temperature	0°C to 40°C
	Humidity	10% to 90% (non-condensing)
DIMENSIONS	(W x H x D mm)	372 x 477 x 279 (with stand) 308 x 372 x 56 (without stand)
WEIGHT	Net	5.7kg (w/stand); 3.4 kg (without stand)
REGULATIONS		TCO'03, TÜV/GS, TÜV/Ergo, ISO 13406-2 (pixel failure class II), TÜV S, UL, cUL, FCC-B (ICES), CB, CE, ICES-003B,NOM, ENERGY, Energy Start, GOST-R, Hygienic, SASO, KTL/MIC, BSMI, CCC, PSB, C-TICK, WEEE.RoHS
POWER MANAGEMENT		Meets TCO'03, ENERGY and Energy Star standards
PACKAGE CONTENTS		LCD display, power cable, 15-pin VGA video cable, DVI cable, Quick Start Guide, ViewSonic Wizard CD-ROM (User Guide/drivers/PerfectSuite software), portrait/pivot CD-ROM software
WARRANTY		Please see: www.viewsoniceurope.com/UK/Support/warranty.htm

ISO 9001 FM 40187 ISO 14001 EMS 40968

ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by the British Standards Institution.

ViewSonic Europe Limited/UK
ViewSonic House
Fleming Way, Crawley
West Sussex, RH10 9GA
United Kingdom

Tel: +44 (0) 12 93 64 39 00
Fax: +44 (0) 12 93 64 39 10

ViewSonic Germany
Hanns-Martin-Schleyer-Straße 18A
47877 Willich
Germany

Tel: +49 (0) 21 54 91 88 0
Fax: +49 (0) 21 54 91 88 10

ViewSonic France
Parc des Barbanniers
1 allée des Bas Tilliers
92230 Gennevilliers
France

Tel: +33 (0) 1 41 47 49 00
Fax: +33 (0) 1 41 47 49 10

ViewSonic Corporation
381 Brea Canyon Road
Walnut
California 91789-0708
USA

Tel: +1 909 869 7976
Fax: +1 909 869 7958

ViewSonic Benelux Tel: +32 056/85 26 27
ViewSonic Denmark Tel: +45 70 22 11 71
ViewSonic Finland Tel: +358 (0)9 54 06 40 70
ViewSonic Italy Tel: +34 (0) 91 63 05 339
ViewSonic MEA Tel: +971 (0) 4 88 11 871
ViewSonic Norway Tel: +47 (0) 22 88 17 60
ViewSonic Spain Tel: +34 (0) 91 63 05 339
ViewSonic Sweden Tel: +46 (0) 8 50 71 30 00

[1] May require optional Mac adapter [2] Requires optional VESA DDC/CI compatible graphics card

Copyright © 2005, ViewSonic Corporation. All rights reserved. Specifications subject to change without notice. Corporate names and trademarks stated herein are the property of their respective companies. VS VP730-10/05-UK